



AVC-ENN41AVT AI

NDA
COMPLIANT | CE | FC



4MP H.265 NETWORK IR EYEBALL CAMERA

OVERVIEW

- H.265 Main Profile Video Compression Technology
- 4MP (2592 x 1520) H.265 Full Real Time Coding
- Max. Resolution: 2592 x 1520
- ICR Auto Switch
- True Day / Night
- Up to 100ft. Night Time Viewing Distance
- 3D DNR, Digital WDR
- Support Auto Zoom and Manual Zoom
- ROI Coding
- Support Local CVBS Video Output and One Way Audio
- Supports Smartphone, iPad, Remote Monitoring
- IP66 Ingress Protection
- Support Three Streams
- DC12V / PoE
- NDA Compliant
- UL-listed

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES



AVM-EDMT-W-TL1
JUNCTION BOX



AVM-EWMT-W-TL1
WALL MOUNT

SPECIFICATIONS

CAMERA																
Image Sensor	1/3" Progressive Scan CMOS															
Image Size	2592 x 1520															
Shutter Speed	1/2s to 1/100,000s															
Iris Type	DC Iris															
Min. Illumination	Color: 0.005 lux @ F1.6(AGC ON); BW: 0 lux with IR															
IR Distance	Up to 164ft															
Lens	Fixed 2.8 - 12 mm @ F1.3 Horizontal FoV: 100.0° ~ 28.9° Vertical FoV: 54.5° ~ 16.7° Diagonal FoV: 104.8° ~ 33.1°															
Lens Mount	Ø14															
Day & Night	ICR															
Backlight Compensation (BLC)	Yes															
Highlight Compensation (HLC)	Yes															
Defog	Yes															
S/N Ratio	≥50dB															
Angle Adjustment	Pan: 0°~360° ; Tilt: 0°~80° ; Rotation:0°~360°															
VIDEO IMAGE																
Video Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub/third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG															
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile															
Resolution	4MP (2592×1520), 2K(2560×1440), 3MP(2304×1296), 1080P(1920×1080), 720P(1280×720), D1, CIF, 480×240, VGA(640×480)															
Main Stream	60Hz: 4MP/2K/3MP/1080P/720P (1~30fps); 50Hz: 4MP/2K/3MP/1080P/720P (1~25fps)															
Sub Stream	60Hz: 720P/D1/CIF/VGA (1~30fps); 50Hz: 720P/D1/CIF/VGA (1~25fps)															
Third Stream	60Hz: D1/480x240/CIF (1~30fps); 50Hz: D1/480x240/CIF (1~25fps)															
Video Bit Rate	64 Kbps ~ 8 Mbps (CBR / VBR Adjustable)															
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser															
ROI	Each ROI to be configured separately															
NETWORK / INTERFACE																
Network	1 x RJ45 10M / 100M Self-Adaptive Ethernet port															
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTMP, RTCP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, HTTP POST, 802.1x, UPnP, HTTPS, QoS															
Interface Protocol	ONVIF (Profile S, G, T, M)															
Web Browser	IE11 (Plug-in required) / Google Chrome 89.0+ / Edge 89.0+ / Firefox 87.0+ / Safari 14.0+															
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission															
Security	Video encryption, firmware encryption, HTTPS encryption, configuration encryption, illegal login lock, IP address filtering, 802.1x authentication, basic and digest authentication for HTTP/RTSP															
Storage	Micro SD/SDHC/SDXC Slot (up to 256GB) with video and still image capture function															
Video Output	No															
Audio	1CH audio input; 1CH built-in MIC															
Audio Compression	G711A / U															
Alarm	N/A															
Hardware Reset	Yes															
DORI DISTANCE																
	<table border="1"> <thead> <tr> <th>Lens</th> <th>Detect</th> <th>Observe</th> <th>Recognize</th> <th>Identify</th> </tr> </thead> <tbody> <tr> <td>2.8 ~ 12mm (W)</td> <td>193.27ft (58.91m)</td> <td>77.29ft (23.56m)</td> <td>38.64ft (11.78m)</td> <td>19.32ft (5.89m)</td> </tr> <tr> <td>2.8 ~ 12mm (T)</td> <td>675.82ft (205.99m)</td> <td>270.34ft (82.40m)</td> <td>135.17ft (41.20m)</td> <td>67.58ft (20.60m)</td> </tr> </tbody> </table>	Lens	Detect	Observe	Recognize	Identify	2.8 ~ 12mm (W)	193.27ft (58.91m)	77.29ft (23.56m)	38.64ft (11.78m)	19.32ft (5.89m)	2.8 ~ 12mm (T)	675.82ft (205.99m)	270.34ft (82.40m)	135.17ft (41.20m)	67.58ft (20.60m)
Lens	Detect	Observe	Recognize	Identify												
2.8 ~ 12mm (W)	193.27ft (58.91m)	77.29ft (23.56m)	38.64ft (11.78m)	19.32ft (5.89m)												
2.8 ~ 12mm (T)	675.82ft (205.99m)	270.34ft (82.40m)	135.17ft (41.20m)	67.58ft (20.60m)												
FUNCTIONS																
Remote Monitoring	Web Browser Interface, Mobile App, AVYCON CVMS 2.0															
Smart Alarm	Motion detection, SD card error, SD card full, IP address conflict, cable disconnection															
Smart Analytics	Line crossing, region intrusion/entrance/exiting, loitering detection, illegal parking detection, abandoned/missing object detection, Target counting by line/intrusion area/heat map, exception detection, face detection and face capture															
Video Metadata	Simultaneously captures human body, motor vehicle and non-motor vehicle and extracts 13 human features, 5 motor vehicle features and 1 non-motor vehicle feature															
General Function	Watermark, video mask, heartbeat, image distortion correction, corridor pattern															
GENERAL																
Power Supply	DC12V / PoE (IEEE802.3af)															
Power Consumption	<9.5W															
Operating Environment	-22°F ~ 140°F (-30°C ~ 60°C) Humidity: less than 95% (non-condensing)															
Storage Environment	-22°F ~ 149°F (-30°C ~ 65°C) Humidity: less than 95% (non-condensing)															
Dimensions (in)	Ø 5.14 x 4.30															
Weight (lb)	Approx. 1.43 lbs															
Ingress Protection	IP 67															
Certificate	CE, FCC, UL															
Installation	Ceiling mounting; Wall mounting															
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU), directive 94/62/EC and REACH (EC1907/2006)															