

AVC-EN91VT

2MP IP EYEBALL IR CAMERA

IP
CAMERA





FUNCTION

- 1080p (1920 x 1080) Full Real Time Coding
- Maximum Resolution: 1920 x 1080
- 2.8~12mm Varifocal Lens
- H.264 / 30 IR LED
- ICR Auto Switch, True Day & Night
- 20~30m IR Night View Distance
- 3D DNR, Digital WDR
- Support Corridor Pattern
- ROI Coding
- PoE (Power over Ethernet) Power Supply
- Support Smart Phone, iPad, Remote Monitoring
- Support P2P / Triple Streams
- Waterproof (IP66)
- DC 12V / White Casing



DIMENSION

*Unit : mm (Inch)



SPECIFICATION

DESCRIPTION	
IMAGE SENSOR	1/3" CMOS
IMAGE SIZE	1920 x 1080
ELECTRONIC SHUTTER	1/25s~1/100000s
MIN. ILLUMINATION	0lux (IR LED ON)
LENS	2.8~12mm Varifocal Lens
LENS MOUNT	CS / ø14
VIDEO COMPRESSION	H.264 / MJPEG
RESOLUTION	1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
MULTI-STREAM	1920x1080 (1~30fps) / 1280x720 (1~30fps) / 1280x720 (1~10fps) / D1 (1~30fps) / CIF (1~30fps) / CIF (1~30fps) / 480x240 (1~30fps)
BIT RATE	64 Kbps~8 Mbps
ENCODE MODE	VBR / CBR
QUALITY	Five Levels Under VBR; Freely Adjustable Under CBR
IMAGE SETTINGS	Corridor pattern, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable through Client Software or Web Browser
REMOTE MONITORING	IE Browsing, CMS Remote Control
ONLINE CONNECTION	Support Simultaneous Monitoring for up to 6 users; Support Multi-Stream Real Time Transmission
PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, Protocol SMTP, FTP
STORAGE	Network Remote Storage
SMART ALARM	Motion Alarm
DAY & NIGHT	ICR
POE	Yes
IR DISTANCE	20~30m
WATERPROOF	IP66
NETWORK	RJ45
AUDIO	No
POWER SUPPLY	DC 12V/PoE
POWER CONSUMPTION	<2.5W
IR CONSUMPTION ON	<5W
OPERATING ENVIRONMENT	-22°F~140°F, 10%~90% Humidity
DIMENSIONS	ø109x130mm (ø4.29x5.12 in)
WEIGHT (NET)	659g (1.45 lbs)