


**AVC-NVP51F180**  
**5MP PANORAMIC 180° MINI DOME NETWORK CAMERA**



**5MP PANORAMIC 180° MINI DOME NETWORK CAMERA**

5MP PANORAMIC 180° MINI DOME CAMERA WITH SMART FEATURES

The AVYCON AVC-NVP51F180 camera is a 5MP 180° Mini Dome Network Camera with Smart Features. This 5MP Panoramic camera supports True Day and Night mode, PoE, and up to 49ft. of Smart IR Illumination. This camera includes a Fixed 1.68mm Lens with Auto-focus capabilities that can be controlled through a DVR. Also standard with this series is Digital NR, ROI, HLC, True WDR, and BLC capabilities along with IP67 outdoor rating. Capable of 180 degrees of motion and recording audio through an advanced built-in microphone and integrated junction box.




**FUNCTIONS**

- 5MP ( 2592 x 1944 ) @ 30fps
- Max. Resolution: 2592 x 1944
- True Day & Night ICR filter Auto Switch
- Up to 49 ft (15 m) IR Illumination
- Fixed 1.68mm Lens
- 3D/2D DNR, Super WDR, HLC, BLC and ROI Encoding
- Supports Triple Streams
- Supports Remote Access with Windows, macOS, iOS and Android
- IP67 Ingress Protection
- Operating Temperature: -40°F - 140°F(-40°~60° C)
- DC12V±10%/ PoE (802 .3af)

**DIMENSIONS**

Unit : inch (mm)



**OPTIONAL ACCESSORIES**



AVM-P-PMT-A1  
POLE MOUNT



AVM-P-CMT-A1  
CORNER MOUNT BRACKET



AVM-DWMT-V180  
WALL MOUNT



# AVC-NVP51F180

## 5MP PANORAMIC 180° MINI DOME NETWORK CAMERA

### SPECIFICATIONS

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Resolution	5MP
Image Size	2592 x 1944
Min. Illumination	Color: 0.005lux @F1.2 or 0.008lux @F2.0   BW: 0lux w IR ON
Shutter Speed	1/100,000s ~ 1s
Slow Shutter	Supported
IR Distance	Up to 49ft. (15m)
Lens	Fixed 1.68mm@F2.0
Field of View	H180°/V95°
WDR	120dB
VIDEO STREAM	
Max. Image Resolution	2592 x 1944
Supported Resolutions	2592 x 1944, 2560 x 1440, 1920 x 1080, 1280 x 720, 640 x 480, 640 x 360, 320 x 240, 704 x 576, 640 x 480, 320 x 192, 320 x 180
Main Stream	2592 x 1944, 2560 x 1440, 1920 x 1080, 1280 x 720
Sub Stream	640 x 480, 640 x 360, 320 x 240
Third Stream	1920 x 1080, 1280 x 720, 704 x 576, 640 x 480, 640 x 360, 320 x 240, 320 x 192, 320 x 180
Video Compression	H.265*/H.265(HEVC)/H.264*/H.264/MJPEG
Video Bit Rate	16 Kbps ~ 16 Mbps (CBR / VBR Adjustable)
NETWORK	
Ethernet	1 x RJ45 10M / 100M Ethernet Port
Network Storage	NAS(Support NFS, SMB/CIFS)
Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
IMAGE	
Day & Night	ICR Filter Auto Switch
True WDR	120dB Super WDR
Digital NR	Yes (3D DNR)
Backlight Compensation (BLC)	Yes
HLC	Yes
ROI	Yes
Privacy Mask	Supported
Sharpness	Yes
Image Setting	Brightness/Contrast/Saturation/Sharpness
VIDEO ANALYTICS	
Smart Events	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed
Alarm Link Events	Motion Detection, Sensor Alarm, SD Card Full, SD Card Error, IP Address Conflict, Network Disconnection
GENERAL	
Housing	Vandal-proof IK10-rated Metal Housing
Power Supply	DC 12V±10% / PoE (802.3af)
Power Consumption	≤6W, 8.5W MAX (With IR on)
Ingress Protection	IP67
Weight	1.88 lbs (853 g)
Working Temperature	-40°~140° F (-40°~60° Celcius)
Dimensions	4.2 in x 5 in (107mm x 127.2 mm)



# AVYCON<sup>®</sup>

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606

email: info@avycon.com

social: @avycon\_aivo

website: avycon.com