


# AVYCON

## NVR DVR AVR-N9208 / N9216 N9200 Standalone NVR



AVR-N9208 / AVR-N9216



**Compatibility :** Supporting Various IP Cameras  
**Capacity :** Max. 80 / 160 Mbps Up to 8 / 16CH  
**Operating System :** Intuitive, Stable and User Friendly  
**Conventional :** Local Live and Playback

### N9200 Standalone NVR (Max. 80Mbps Up to 8CH)

# SPECIFICATION

MODEL	AVR-N9208	AVR-N9216
OPERATING SYSTEM	EMBEDDED LINUX	
OS FIRMWARE	LINUX OS IN FLASH MEMORY	
MEMORY	2GB DDR3 MEMORY	
VIDEO INPUT	8	16
VIDEO OUTPUT	COMPOSITE : 1	
VGA	1 PORT ( MAX. 1920 X 1080)	
HDMI	1 PORT ( MAX. 1920 X 1080)	
SPOT OUTPUT	COMPOSITE : 1	
THROUGHPUT	80Mbps	160Mbps
AUDIO INPUT / OUTPUT	4 INPUT / 1 OUTPUT	
ALARM INPUT	4 + MASTER ALARM	
ALARM OUTPUT	4 (TTL) / 2 (RELAY)	
USB 2.0	4 X USB (2 X FRONT PANEL, 2 X REAR PANEL)	
ETHERNET	10 / 100 / 1000 Mbps ETHERNET (RJ-45) X 2	
USER INTERFACE (GUI / CONTROL DEVICE)	KEYPAD, MOUSE, PTZ CONTROL	
ARCHIVE FILE FORMAT	EXE (VIDEO CLIP) / AVI (VIDEO CLIP) / JPEG (STILL IMAGE)	
NTP SERVER	YES	
GMT TIME ZONE	YES	
AUTO DST	YES	
RECORDING MODES	CONTINUOUS / ALARM / EMERGENCY	
PRE-ALARM RECORDING	UP TO 10 MINUTES / USER PROGRAMMABLE	
PLAYBACK CONTROL	X1, X2, X4, X8, X16, X32, X64	
PTZ CONTROL	RS-485 / 422 SERIAL PORT 1 (TERMINAL BLOCK)	
TEXT INSERTION (POS)	4	
MULTI LANGUAGE	ENGLISH / FRENCH / JAPANESE / KOREAN / RUSSIAN / FINNISH / TURKISH / DUTCH / CHINESE / VIETNAMESE / THAI / SPANISH / GERMAN / PORTUGUESE / ARABIC / ITALIAN	
CENTRAL MONITORING STATION	CMS PRO (WINDOWS) / ICMS (MAC) / WEB CLIENT PRO	
MOBILE VIEWER	IPAD / IPHONE / ANDROID	
PRIMARY STORAGE	2 X SATA HDD	
CLIP COPY STORAGE	USB MEMORY STICK	
DIMENSION (WXHXD)	430 mm x 88 mm x 380 mm / 16.93 inch x 14.96 inch x 14.96 inch (RACK TYPE)	
OPERATING TEMPERATURE	5°C ~ 40°C / 41°F ~ 104°F	
OPERATING HUMIDITY	0% ~ 90%	
POWER ADAPTER	12V, 6A (72W)	

\* Design and specifications are subject to change without notice.

## DIMENSION



## SYSTEM INTERCONNECTION

