

AVR-N932P SERIES

AVYCON



MODEL		AVR-N932P8	AVR-N932P16
SYSTEM	COMPRESSION	STANDARD H.264 / MPEG4	
	CPU	CORTEX A9	
	OS	EMBEDDED LINUX	
VIDEO	OUTPUT	VGA X 1:1080P HDMI X 1:1080P	
IP INPUT	RESOLUTION	3MP / 1080P / 960P / 720P	
	CPU	32 CH 3MP / 1080P / 960P / 720P @30 FPS	
AUDIO	INPUT	32 CH IPC INPUT	
	OUTPUT	RCA X 1	
	2-WAY AUDIO	RCA X 1	
RECORD	RESOLUTION	3MP : 2048 X 1536, 1080P : 1920 X 1080 960P : 1280 X 960, 720P : 1280 X 720 D1 : 704 X 576	
	FRAME RATE	800 FPS (PAL) 960 FPS (NTSC)	
	BIT RATE	256Kbps ~ 12Mbps	
	ENCODE	VBR / CBR	
	QUALITY	6 LEVEL	
	MODE	MANUAL, TIMER, MOTION, SENSOR	
PLAYBACK	FILE MANAGER	LOCK, UNLOCK, RESERVING TIME	
	PLAYBACK	16 CH	
	SEARCH	TIME/CALENDAR SEARCH, EVENT (MOTION,EXTERNAL ALARM)	
ALARM	SMART SEARCH	APPLY DIFFERENT COLORS TO DISPLAY WHETHER A CHANNEL IN A PERIOD OF TIME RECORDING OR NOT	
	FUNCTION	PLAY, PAUSE, FF, FB, DIGITAL ZOOM	
	MODE	SENSOR, MOTION, VIDEO LOSS	
NETWORK	INPUT	4 CH LOCAL INPUT, SUPPORT IPC ALARM INPUT	16 CH LOCAL INPUT, SUPPORT IPC ALARM INPUT
	OUTPUT	1 CH	4 CH
	TRIGGERING	RECORD, ALARM OUT, E-MAIL, ETC	
MOBILE VIEWER	INTERFACE	GMAC X 1	
	POE	RJ45 X 8	RJ45 X 16
	PROTocal	TCP / IP, UDP, DHCP, DNS, PPPOE, DDNS, E-MAIL	
PORT	OTHERS	18 USERS ONLINE, DUAL STREAM	
	OS	IPHONE, ANDRIOD	
OTHERS	FUNCTION	MULTI-SCREEN SURVEILLANCE, RECORD, SNAPSHOT, PTZ CONTROL, SAVE THE DEVICE LIST	
	HDD	SATA X 2	SATA X 8
	RS485	RS 485 X 1, SUPPORT PTZ AND KEYBOARD	
DIMENSIONS	USB	USB 3.0 X 1, USB 2.0 X 1, ONE FOR MOUSE, ANOTHER FOR USB BACKUP DEVICE	
	REMOTE CONTROLLER	YES	
	POWER SUPPLY	ATX	
WORK ENVIRONMENT	430 mm x 300 mm x 55 mm (W X D X H)		430 mm x 450 mm x 89 mm (W X D X H)
		-10°C ~ 55°C, 10% ~ 90% HUMIDITY	

