

AVR-T932

32CH HD ALL-IN-ONE DVR

ALL-IN-ONE

• HD-TVI • CVI • AHD • 960H • ANALOG • IP



HD OVER COAX & UTP



H.264 HIGH PROFILE



HDMI



DDNS



P2P CLOUD

Features

- 32 CH All-in-One 1080P DVR, HD-TVI, CVI, AHD (1080P/720P), Analog (Auto-Detect)
- 16 CH Audio, HDD up to 48TB
- HDMI, VGA, BNC (CVBS Spot)
- HD-TVI, CVI, AHD, Analog (Auto-Detect), and IPC Input
- 1080P / 720P / 960H (WD1) Hybrid Live & Playback
- 30FPS @ 720P & 1080P-Lite / 12FPS @ 1080P Recording
- Pentaplex Operation: Live, Record, Playback, Backup, and Network
- New Innovative Graphical User Interface Menu
- Multi-Mode Hybrid Recording: Continuous, Motion, Manual (Override)
- Various Search Features: Smart, Time, Calendar, Event (Motion), Thumbnail (Time-Sliced Image)
- Archiving options: USB, IE Browser, Safari, and CVMS Software
- P2P Technology - Scan, Connect, and View (No Port Forwarding)
- DHCP, DDNS, PPPoE Network Protocol, IE Browser and CVMS
- Dual Stream Technology to work with various network environments
- Multi-User Log-in with Individual Privileges
- HDMI & VGA Simultaneous Monitor Output (up to 1080P)
- PTZ Presets, Tours, and OSD Menu: up to 255 Presets and 8 Tours
- Mobile Viewing App: Mobile CVMS (Apple & Android)
- Client Software: CVMS (Windows), NVMS-1200 (Mac OS)
- HD Video over Coax up to 1500ft without a repeater, and up to 800ft over UTP Cable with Passive HD-TVI Baluns (AVA-TVI-BLN)
- Backward compatible with existing Analog, 960H, and 1000TVL Cameras

Dimensions

Unit: mm(inch)



Rear Panel



Specification

SYSTEM	Compression	Standard H.264 High Profile
	CPU	Cortex A9
	OS	Embedded Linux
VIDEO	Input	32 BNC (No IP)
	Output	HDMI & VGA : 1920 x 1080, BNC Output
AUDIO	Input	1 CH
	Output	RCA x 1
	Communication	2 Way audio
RECORD	Resolution	1080P (1920 x 1080), 720P (1280 x 720), 960H (960 x 480)
	720P	960fps (NTSC) 800fps (PAL)
	1080P	480fps (NTSC) 400fps (PAL)
	Bitrate	1 ~ 6 MBPS
	Encode	VBR / CBR
	Quality	6 Level
	Mode	Manual, Timer, Motion, Sensor
INPUT	Resolution	3MP / 1080P / 960P / 720P / WD1 / D1
	Frame rate (fps)	3MP: 15fps (NTSC) / 12fps (PAL), 1080P / 960P / 720P: 30fps (NTSC) / 25fps (PAL) Per Channel
PLAYBACK	Playback	8 CH
	Search	Time / Calendar search, Event (Motion, External alarm)
	Smart Search	Highlighted date and time to display the recorded channels
	Function	Play, Pause, FF, FB, Digital zoom, etc.
ALARM	Mode	Sensor, Motion, Video loss
	Input	16 CH
	Output	4 CH
	Triggering	Record, PTZ Preset, Alarm out, E-mail, etc.
NETWORK	Interface	RJ45 10M / 100M / 1000M adaptive Ethernet network port
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
	Users	10 Users online, Dual Stream
	MOBILE VIEWER	Application
I/O	Function	Live, Search, Playback, Grouping, and etc.
	HDD	SATA x 8 (UP TO 48TB)
	RS485	RS 485 x 2 (One for PTZ / one for keyboard)
	USB	USB 2.0 x 2 (One for mouse / one for USB backup)
	IR Controller	Optional
PHYSICAL	Power supply	ATX
	Consumption	<40W (Without HDD)
	Dimensions (mm)	430mm x 450mm x 89mm (W x H x D)
	Work Environment	14°F ~ 122°F (-10°C ~ 50°C), 10% ~ 90% Humidity

Available HDD Options

- 1TB HDD: AVR-T932-1T
- 2TB HDD: AVR-T932-2T
- 3TB HDD: AVR-T932-3T
- 4TB HDD: AVR-T932-4T
- 6TB HDD: AVR-T932-6T
- 8TB HDD: AVR-T932-8T
- 12TB HDD: AVR-T932-12T
- 16TB HDD: AVR-T932-16T
- 20TB HDD: AVR-T932-20T
- 24TB HDD: AVR-T932-24T
- 28TB HDD: AVR-T932-28T
- 32TB HDD: AVR-T932-32T
- 36TB HDD: AVR-T932-36T
- 42TB HDD: AVR-T932-42T
- 48TB HDD: AVR-T932-48T

Mobile App

AVYCON Mobile CVMS

