

AVR-T932A

32CH HD ALL-IN-ONE DVR

ALL-IN-ONE

• HD-TVI • CVI • AHD • 960H • ANALOG • IP



FEATURES

- 32 CH All-in-One 1080P DVR, HD-TVI, CVI, AHD (1080P / 720P), Analog (Auto-detect), and IP
- 4 ONVIF® IPC Support (CH 33 - 36)
- 16 CH Audio, HDD Up to 64 TB
- HDMI, VGA, BNC (CVBS Spot)
- 2 e-SATA Port
- 2U, 19" Rack Mountable
- HDMI, VGA, BNC (CVBS Spot)
- HD-TVI, CVI, AHD, Analog (Auto-detect), and IPC Input
- 1080P / 720P / 960H (WD1) Hybrid Live & Playback
- 30fps @ 720P & 1080P-Lite / 12fps @1080P Recording
- Pentaplex Operation: Live, Record, Playback, Backup, and Network
- New innovative Graphical User Interface Menu
- Multi-Mode Hybrid Recording: Continuous, Motion, Manual (Override)
- Various Search Fetures: Smat, Time, Calendar, Event (Motion), Thumbnail (Time-Sliced Image)
- Archiving options: USB, IE Browser, Safari, and CVMS Software
- P2P Technology - Scan, Conect, and View (No Port Forwarding)
- DHCP, DDNS, PPPoE Network Protocol, IE Browser and CVMS
- Dual Stram Technology to work with various network environments
- Multi-User Log-in with individual Privileges
- HDMI & VGA Simultaneous Monitor Output (Up to 1080P)
- PTZ Presets, Tours, and OSD Menu: Up to 255 Presets and 8 Tours
- Mobile Viewing App: Mobile CVMS (Apple® and Android®)
- Client Software: CVMS (Windows), NVMS-1200 (Mac OS)
- HD Video over Coax up to 1500ft. without a repeater, and up to 800ft. over UTP Cable with Passive HD-TVI Baluns (AVA-TVI-BLN)
- Backward compatible with existing Analog, 960H, and 1000TVL Cameras

DIMENSIONS

Unit: mm (inch)



REAR PANEL



SPECIFICATIONS

SYSTEM	Compression	Standard H.264 High Profile
	CPU	Cortex A9
	OS	Embedded Linux
VIDEO	Input	BNC × 32
	Resolution	TVI / AHD 1080P, 720P, WD1 Real time
	Output	HDMI × 1: 1920 × 1080, VGA × 1: 1920 × 1080, BNC × 1: CVBS (Used as the main or spot output)
AUDIO	Input	RCA × 16 CH
	Output	RCA × 1 CH
	Two-way audio	Take up channel one audio input
RECORD	Resolution	1080P, 1080P lite, 720P, WD1
	Frame Rate	1080P: 12fps (PAL) / 15fps (NTSC) 1080P lite / 720P / WD1: 25fps (PAL) / 30fps (NTSC)
	Bit Rate	768Kbps ~ 8Mbps
	Mode	Manual, Timer, Motion, Sensor
PLAYBACK	Playback	16 CH
	Search	Time slice / Time / Event / Tag search
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, Pause, FF, FB, Digital Zoom, etc.
ALARM	Mode	Manual, Sensor, Motion, Exception
	Input	16
	Output	4
	Triggering	Record, Snap, Preset, E-mail, etc.
NETWORK	Interface	RJ45 10M / 100M / 1000Mbps × 1
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
	Web Client	Multiple Online Users
MOBILE	OS	iOS, Android®
STORAGE	HDD	SATA × 8, Max. 8TB per HDD
BACKUP	Local Backup	U Disk, USB Removable HDD
	Network Backup	Yes
PORT	RS485	RS485 × 2, Connect to PTZ and keyboard
	USB	USB 2.0 × 1, USB 3.0 × 1
	Remote Controller	Optional
OTHERS	Power Supply	ATX 250W
	Consumption	≤ 20W (Without HDD)
	Dimensions (mm)	430mm × 450mm × 89mm (W × D × H)
	Work Environment	14°F ~ 122°F (-10°C ~ 50°C), 10% ~ 90% Relative Humidity

AVAILABLE HDD OPTIONS

- 1TB HDD: AVR-T932A-1T
- 2TB HDD: AVR-T932A-2T
- 3TB HDD: AVR-T932A-3T
- 4TB HDD: AVR-T932A-4T
- 6TB HDD: AVR-T932A-6T
- 8TB HDD: AVR-T932A-8T
- 12TB HDD: AVR-T932A-12T
- 16TB HDD: AVR-T932A-16T
- 24TB HDD: AVR-T932A-24T
- 32TB HDD: AVR-T932A-32T
- 36TB HDD: AVR-T932A-36T
- 42TB HDD: AVR-T932A-42T
- 48TB HDD: AVR-T932A-48T
- 56TB HDD: AVR-T932A-56T
- 64TB HDD: AVR-T932A-64T

MOBILE APP

AVYCON Mobile CVMS



AVYCON®

☎ 949-752-7606 🌐 www.avycon.com ✉ info@avycon.com

Copyright © AVYCON. All Rights Reserved. Design and specifications are subject to change without notice.