AVR-TS504A





FEATURES

- 4 Channels HD-TVI/CVI/AHD High Definition Input
- Up to 4 Channels 5MP / 4MP / 4MP Lite / 3MP / 1080P / 960P / 720P / WD1 Recording
- 1 Channel IP 3MP / 1080P / 960P / 720P Recording
- Utilizes the H.264 High Profile Compression format to ensure high quality video at lower bitrate
- Intuitive and user-friendly Graphic User Interface (GUI) with full operation by mouse.
- Multiple Recording Modes: Manual, Scheduled, Motion and Sensor.
- Playback: 4 Channels Simultaneous
- Search: Search by Time Slice, Time, Event (Manual, Sensor, Motion), Tag Search
- Quick and Intuitive Backup via USB and Network
- Pentaplex Operation: Can simultaneously allow Preview, Record, Playback, Backup and Remote Access from different users.
- Network functions such as DHCP, DDNS, PPPoE protocols supported and also access with CMS clients
- Remote Access using Internet Explorer/Safari or CVMS: Live Preview, Playback, Backup, PTZ and System Configuration
- Dual Streams Recording allows for full High Definition recording to hard drive while supplying a lower resolution for remote viewing with mobile devices and computers.
- Supports multiple online users
- User management, Log Viewing and Device Status
- Up to HDMI 2K Output display (with supported 2K monitors)
- Supports PTZ Presets and Auto Cruise Up to 255 Presets and 8 Cruises
- NAT and QR Code functionality allows remote access with mobile devices and computers without the need for port-forwarding
- Powerful Mobile Apps for mobile devices and tablets available on iOS and Android® OS

DIMENSIONS

Unit: mm (inch)



REAR PANEL



SPECIFICATIONS

SYSTEM	Compression	Standard H.264 High Profile
	CPU	Cortex A7
	OS	Embedded Linux
VIDEO	Input	BNC × 4
	Resolution	TVI / AHD : 5MP @ 20fps; 4MP, 3MP, 1080P, 720P, WD1 Real Time
		CVI : 1080P, 720P Real Time
	IP Input /	IPC × 1 / 6Mbps
	Access Bandwidth	
	Output	HDMI × 1 : 2560 × 1440, 1920 × 1080, 1280 × 1024
		VGA × 1 : 1920 × 1080, 1280 × 1024
		BNC \times 1 : CVBS (Used as the main or spot output)
AUDIO	Input	RCA × 4 CH
	Output	RCA × 1 CH
	Two-way Audio	Take up channel one audio input
RECORD	Resolution	5MP, 4MP, 4MP Lite, 3MP, 1080P, 720P, WD1
	Frame Rate	5MP : 10fps (PAL / NTSC)
		4MP / 3MP : 12fps (PAL) / 15fps (NTSC)
		4MP Lite / 1080P / 720P / WD1: 25fps (PAL) / 30 fps (NTSC)
	Bit Rate	768Kbps ~ 8Mbps
	Mode	Manual, Timer, Motion, Sensor
IP INPUT	Resolution	4MP / 3MP / 1080P / 960P / 720P
	Frame Rate	25fps (PAL) / 30fps (NTSC)
PLAYBACK	Playback	Maximum 4 Channels
	Search	Time Slice / Time / Event / Tag Search
	Smart Search	Highlighted color to display the camera record in a certain
		period of time, different colors refers to different record events
	Function	Play, Pause, FF, FB, Digital Zoom, etc.
ALARM	Mode	Manual, Sensor, Motion, Exception
	Input	4
	Output	1
	Trigger Actions	Record, Snap, Preset, E-mail, etc.
NETWORK	Interface	RJ45 10 / 100Mbps × 1
	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
	Web Client	Multiple Online Users
MOBILE	OS	iOS, Android®
DEVICE		
STORAGE	HDD	SATA × 1, Max. 8TB per HDD
BACKUP	Local Backup	USB Flash Drive, USB Mobile HDD
	Network Backup	Yes
PORT	RS485	RS485 × 1, Connect To PTZ or Keyboard
	USB	USB 2.0 x 2: 1 Front Panel and 1 Rear Panel
	Remote Controller	Yes
OTHERS	Power Supply	DC 12V
	Consumption	≤ 5W (Without HDD)
	Dimensions (mm)	295mm x 42mm x 246mm (W x H x D)
	Work Environment	-4°F ~ 122°F (-20°C ~ 50°C), 10% ~ 90% Relative Humidity

AVAILABLE HDD OPTIONS

- 1TB HDD: AVR-TS504A-1T
- 4TB HDD: AVR-TS504A-4T • 6TB HDD: AVR-TS504A-6T

• 8TB HDD: AVR-TS504A-8T

- 2TB HDD: AVR-TS504A-2T
- 3TB HDD: AVR-TS504A-3T

MOBILE APP

AVYCON Mobile CVMS







Copyright © AVYCON. All Rights Reserved. Design and specifications are subject to change without notice

OTHERS Power Sup Consumpti Dimensions

42mm (1.65")